



The VCMA-15ULS is ideal for automatic collection and removal of condensate from air conditioning, refrigeration and de-humidification equipment when gravity drainage is not possible or practical.

Item: 554405

Model: VCMA-15ULS

Electrical

HP	1/50 hp
Frequency	60 Hz
Amps - Full Load	1 A
Full Load Watts	60 W
Volts	115 VAC
Cord Length	6 ft / 1.83 m
Continuous Duty	No

Operation

Max Flow Rate - 60 Hz	1.08 gpm / 65 gph / 246 Lph / 4.1 Lpm / 0.25 m ³ /h
Flow Rate At 1ft	1.08 gpm / 65 gph / 246 Lph / 4.1 Lpm / 0.25 m ³ /h
Max PSIG	6.5 PSI
Shut-Off	15 ft / 4.57 m
Maximum Suction Lift	4.5 Meter
† Handling Size	0" / 0 cm
Safety Switch	YES

Max Fluid Temperature	75°F
-----------------------	------

Materials of Construction

Pump Base Material	Plastic
Pump Body Material	Plastic
Impeller Type	Semi-open
Impeller Material	GF Polypropylene
Check Valve	Yes

Installation

Discharge Thread	Barb
Discharge Type	Barb
Discharge	0.38 "
Suction Type	Screened
Product Weight	4.4 lb / 2 kg
Product Width	5 " / 12.7 cm
Product Height	7.03 " / 17.86 cm
Product Length	11 " / 27.94 cm
Pump Length	11 " / 27.94 cm
Product Weight w/ Pack	5 lb / 2.27 kg
Carton Width	5 " / 12.7 cm
Carton Height	7.13 " / 18.1 cm
Carton Length	12 " / 30.48 cm
Tubing Included	No

Other

Accessories Included	Removable 3/8" barbed check valve
Electrical Agency Approvals	CSA/UL
Standard Warranty	12 Months
	Warranty Terms and Conditions Link