

NOVOCLEAR 485HE SERIES WATER FILTERS

Problem water is no problem with our full line of NovoClear 485 Water Filters. Eliminate iron, sediment, bad tastes, stains and odors, as well as, color caused by organics. The high-efficiency control valve monitors water usage and flushes the system automatically, readying it for operation again

- ➔ **Taste & Odor Filters:** Chlorine and organic matter can make your water smell and taste terrible. The **Novo Clear 485 Taste & Odor filter** uses high-quality granular activated carbon to absorb the problem-causing substances.
- ➔ **Chloramine removal Filters:** Chloramines are now commonly used to disinfect municipal water supplies causing taste & odor problems. To remove chloramines a special catalytically enhanced carbon is required.
- ➔ **Multi Media Filters:** Cloudy water means you likely have suspended silt: or sediment. Restore your water to crystal clear as the **NovoClear 485 Multi-Media** filter traps particulate matter as small as 20 microns.
- ➔ **Nexsand Turbidity Filters:** Remove suspended solids, Ferric Hydroxide (Red Water Iron) or Sediment from your well or water system down to 5 Microns. Nexsand has proven extremely effective and will double the service flow of Multi Media or Sand Filters.
- ➔ **Neutralizing Filters:** The **NovoClear 485 Neutralizing** filters raise the pH of acidic water to neutralize corrosiveness protecting fixtures, pipes and appliances.
- ➔ **Iron & Sulfur Filters:** Water comes in contact with manganese greensand causing oxidization into solids which can be trapped in the filter bed

Features:

- ➔ Exclusive NSF Certified control valve with reliable electronic sensors, adjustable cycle time and proven piston, seal & spacer design
- ➔ NSF Certified fibreglass pressure tank
- ➔ Tank jackets reduce condensation. Standard on 8", 9" & 10" tanks
- ➔ User-friendly backlit LCD display
- ➔ Simple set up and programming with no confusing codes or symbols to remember
- ➔ Automatic Vacation Mode prevents media cementing
- ➔ "No Touch" LCD information display rotates key info like last regeneration date, current flow rate & peak flow rate
- ➔ Unique, compact one piece bypass with integrated turbine meter
- ➔ Time saving quick connect fittings on bypass, drain & brine line. Even the power cord has quick connects
- ➔ Drain line o-ring. No need for Teflon
- ➔ Audible Cycle Advance Alarm
- ➔ 48 hour self charging battery back-up
- ➔ Meter with Day Over ride
- ➔ Includes hose clamp and 10' of drain tubing



Chloramine (CLA) Units use Two Tank System for effective reduction of chloramines



7 Year Warranty Control Valve



Lifetime Warranty Pressure tank



Specifications	NVO485MM-75	NVO485MM-100	NVO485MM-150	NVO485MM-200	NVO485MM-300
	15054001	15054002	15054003	15054004	15054005
Normal Service Flow Rate	4.0 gpm	5.0 gpm	7.0 gpm	10.0 gpm	12.0 gpm
Peak Service Flow Rate	5.0 gpm	7.0 gpm	10.0 gpm	12.0 gpm	15.0 gpm
Micron Rating	15-20 micron	15-20 micron	15-20 micron	15-20 micron	15-20 micron
Backwash Flow Rate	4.0 gpm	5.0 gpm	7.0 gpm	10.0 gpm	14.0 gpm
Filter Media Volume - Cubic Feet	0.75 ft ³	1.0 ft	1.5 ft	2.0 ft	3.0 ft
Filter Tank Size	8x44	9x48	10x54	12x52	14x65
Tank Jacket / Media Loaded	Yes	Yes	Yes	No	No
Shipping Weight	79 lbs	118 lbs	144 lbs	198 lbs	342 lbs

Specifications	NVO485TO-75	NVO485TO-100	NVO485TO-150	NVO485TO-200	NVO485TO-300
	15054006	15054007	15054008	15054009	15054010
Normal Service Flow Rate	4.0 gpm	5.0 gpm	7.0 gpm	10 gpm	12.0 gpm
Peak Service Flow Rate	5.0 gpm	7.0 gpm	10.0 gpm	12.0 gpm	15.0 gpm
Backwash Flow Rate	3.5 gpm	4.0 gpm	5.0 gpm	7.0 gpm	10.0 gpm
Filter Media Volume - Cubic Feet	0.75 ft ³	1.0 ft	1.5 ft	2.0 ft	3.0 ft
Filter Tank Size	8x44	9x48	10x54	12x52	14x65
Tank Jacket / Media Loaded	Yes	Yes	Yes	No	No
Shipping Weight	50 lbs	60 lbs	78 lbs	95 lbs	138 lbs

Specifications	NVO485NU-75	NVO485NU-100	NVO485NU-150	NVO485NU-200	NVO485NU-300	NVO485NUCALC-100	NVO485NUCALC-150
	15054011	15054012	15054013	15054014	15054015	15054040	15054041
Normal Service Flow Rate	2.0 gpm	3.0 gpm	5.0 gpm	6.0 gpm	7.0 gpm	3.0 gpm	5.0 gpm
Peak Service Flow Rate	3.5 gpm	5.0 gpm	8.0 gpm	10.0 gpm	12.0 gpm	5.0 gpm	8.0 gpm
pH Correction Range	6.0 - 6.9 TDS >200	6.0 - 6.9 TDS >200	6.0 - 6.9 TDS >200	6.0 - 6.9 TDS >200	6.0 - 6.9 TDS >200	6.0 - 6.9 TDS <200	6.0 - 6.9 TDS <200
Backwash Flow Rate	3.5 gpm	4.0 gpm	5.0 gpm	7.0 gpm	10.0 gpm	4.0 gpm	5.0 gpm
Filter Media Volume - Cubic Feet	0.75 ft ³	1.0 ft	1.5 ft	2.0 ft	3.0 ft	1.0 ft	1.5 ft
Filter Tank Size	8x44	9x48	10x54	12x52	14x65	9x48	10x54
Tank Jacket / Media Loaded	Yes	Yes	Yes	No	No	Yes	Yes
Shipping Weight	93 lbs	120 lbs	164 lbs	207 lbs	330 lbs	120 lbs	164 lbs

Specifications	NVO485IS-75	NVO485IS-100	NVO485IS-150	NVO485IS-200	NVO485IS-300
	15054016	15054017	15054018	15054019	15054020
Normal Service Flow Rate	3.0 gpm	3.0 gpm	4.0 gpm	5.0 gpm	6.0 gpm
Peak Service Flow Rate	4.0 gpm	5.0 gpm	8.0 gpm	10.0 gpm	12.0 gpm
Backwash Flow Rate	3.5 gpm	4.0 gpm	5.0 gpm	7.0 gpm	10.0 gpm
Compensated Iron Removal Capacity	4,500 ppm	6,000 ppm	9,000 ppm	12,000 ppm	18,000 ppm
KMnO ₄ per Regen	4 oz	4 oz	4 oz	8 oz	8 oz
Filter Media Volume - Cubic Feet	0.75 ft ³	1.0 ft	1.5 ft	2.0 ft	3.0 ft
Filter Tank Size	8x44	9x48	10x54	12x52	14x65
Tank Jacket / Media Loaded	Yes	Yes	Yes	No	No
Shipping Weight	113 lbs	129 lbs	179 lbs	233 lbs	352 lbs
Maximum Combination of Iron X 1, Manganese X 2, H ₂ S X 3		10.0 ppm	Maximum Hydrogen Sulfide		3.0 ppm
Maximum Iron (Ferrous)		7.0 ppm	Maximum Manganese		5.0 ppm
Bacterial Iron		0.0 ppm	Minimum pH		7.0

Specifications	NVO485NEX-75	NVO485NEX-100	NVO485NEX-150	NVO485NEX-200
	15054029	15054030	15054033	15044034
Normal Service Flow Rate	4.0 gpm	5.0 gpm	8.0 gpm	10.0 gpm
Peak Service Flow Rate	7.0 gpm	8.0 gpm	10.0 gpm	12 gpm
Micron Rating	3-5 micron	3-5 micron	3-5 micron	3-5 micron
Backwash Flow Rate	5.0 gpm	7.0 gpm	10.0 gpm	14.0 gpm
Filter Media Volume - Cubic Feet	0.75 ft ³	1.0 ft	1.5 ft	2.0 ft
Filter Tank Size	8x44	9x48	10x54	12x52
Tank Jacket	Yes	Yes	Yes	No
Shipping Weight	90 lbs	135 lbs	205 lbs	255 lbs

Specifications	NVO485CLA-75	NVO485CLA-100	NVO485CLA-150	NVO485CLA-200
	15054035	15054036	15054037	15054038
Recommended Flow Rates	4.0 gpm	5.0 gpm	7.5 gpm	10.0 gpm
Backwash Flow Rate	3.5 gpm	4.0 gpm	5.0 gpm	7.0 gpm
Filter Media Volume - Cubic Feet	1.5 ft ³	2.0 ft	3.0 ft	4.0 ft
Filter Tank Size (qty 2)	8x44	9x48	10x54	12x52
Tank Jacket	Yes	Yes	Yes	No
Shipping Weight	100 lbs	120 lbs	155 lbs	190 lbs
Carbon Type	Canature Catalytic Carbon			

All Filters	
Plumbing Connections	3/4" and 1" connections
Electrical Requirements	Input 120V 60 Hz - Output 12V 650mA
Water Temperature	Min 39 - Max. 100 degrees Fahrenheit
Water Pressure	Min. 20 - Max. 125 psi



Designed, Engineered & Assembled in the U.S.A.

Your Local Plumbing Professional

Toll Free: 1- 877-288-9888
www.novowater.com

Regina, SK • Cambridge, ON • Carmel, IN
 Phoenix, AZ • Pottstown, PA • Guadalajara, MX

A Division of



BEAUTY HEALTH & HOME

80160039 02/12/19

