Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

Taq

RD-100 Large Area Roof Drain

Specification

Watts RD-100 epoxy coated cast iron roof drain with flashing clamp with integral gravel stop, self-locking polyethylene dome (standard), and no hub (standard) outlet.

Suffi	Pipe Sizing x Description	
2	2"(51) Pipe Size (NH Only)	
3	3"(76) Pipe Size	
4	4"(102) Pipe Size	
5	5"(127) Pipe Size (NH Only)	
6	6"(152) Pipe Size	
Suffi	Outlet Type x Description	1 P
NH	No Hub (MJ)	
Р	Push On	
Т	Threaded	
Х	Inside Caulk	1
Suffix	Options Description	Optional Body Material Suffix Description
Suffix -13		
	Description	Suffix Description
-13	Description Galvanized Body & Clamp	Suffix Description -60 PVC Body w/Socket Outlet
-13 -A	Description Galvanized Body & Clamp Accutrol Flow Restrictor	Suffix Description -60 PVC Body w/Socket Outlet
-13 -A -B	Description Galvanized Body & Clamp Accutrol Flow Restrictor Sump Receiver	Suffix Description -60 PVC Body w/Socket Outlet
-13 -A -B -D -F	Description Galvanized Body & Clamp Accutrol Flow Restrictor Sump Receiver Underdeck Clamp	Suffix Description -60 PVC Body w/Socket Outlet
-13 -A -B -D -F	Description Galvanized Body & Clamp Accutrol Flow Restrictor Sump Receiver Underdeck Clamp Deck Flange/Adj. Extension	Suffix Description -60 PVC Body w/Socket Outlet -61 ABS Body w/Socket Outlet Deck Opening 10"(254) with Sump Receiver 13 1/4"(337) Free Area
-13 -A -B -D -F -GSS	Description Galvanized Body & Clamp Accutrol Flow Restrictor Sump Receiver Underdeck Clamp Deck Flange/Adj. Extension Stainless Steel Ballast Guard	Suffix Description -60 PVC Body w/Socket Outlet -61 ABS Body w/Socket Outlet Deck Opening 10"(254) with Sump Receiver 13 1/4"(337) Free Area Sq. In.
-13 -A -B -D -F -GSS -K4	Description Galvanized Body & Clamp Accutrol Flow Restrictor Sump Receiver Underdeck Clamp Deck Flange/Adj. Extension Stainless Steel Ballast Guard Ductile Iron Dome	Suffix Description -60 PVC Body w/Socket Outlet -61 ABS Body w/Socket Outlet Deck Opening 10"(254) with Sump Receiver 13 1/4"(337) Free Area
-13 -A -B -D -F -GSS -K4 -K13	Description Galvanized Body & Clamp Accutrol Flow Restrictor Sump Receiver Underdeck Clamp Deck Flange/Adj. Extension Stainless Steel Ballast Guard Ductile Iron Dome Galvanized Dome	Suffix Description -60 PVC Body w/Socket Outlet -61 ABS Body w/Socket Outlet Deck Opening 10"(254) with Sump Receiver 13 1/4"(337) Free Area Sq. In.
-13 -A -D -F -GSS -K4 -K13 -K40	Description Galvanized Body & Clamp Accutrol Flow Restrictor Sump Receiver Underdeck Clamp Deck Flange/Adj. Extension Stainless Steel Ballast Guard Ductile Iron Dome Galvanized Dome Ductile Iron Low Dome (4" High)	Suffix Description -60 PVC Body w/Socket Outlet -61 ABS Body w/Socket Outlet Deck Opening 10"(254) with Sump Receiver 13 1/4"(337) Free Area Sq. In.
-13 -A -B -D -F -GSS -K4 -K13 -K40 -K80	Description Galvanized Body & Clamp Accutrol Flow Restrictor Sump Receiver Underdeck Clamp Deck Flange/Adj. Extension Stainless Steel Ballast Guard Ductile Iron Dome Galvanized Dome Ductile Iron Low Dome (4" High) Aluminum Dome	Suffix Description -60 PVC Body w/Socket Outlet -61 ABS Body w/Socket Outlet Deck Opening 10"(254) with Sump Receiver 13 1/4"(337) Free Area Sq. In.





The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (800) 338-2581 • F: (828) 248-3929 • Watts.com Canada: T: (888) 208-8927 • F: (905) 481-2316 • Watts.ca Latin America: T: (52) 55-4122-0138 • Watts.com

2" External Water Dam

Side Outlet (2", 3", 4" Only)

Fixed Extension (2", 3", 4")

Adjustable Internal Water Dam

-R

-SO

-V

-W