

FIRESTOPS

PRODUCT INFORMATION BULLETIN

The IPEX Complete System Advantage – including Firestops

IPEX offers a complete line of firestopping products that are easy to install and assist in preventing the passage of flame, smoke or elevated heat transfer through construction joints in fire-rated floors and walls.

Firestops from IPEX are tested to ULC/CAN4 – S115 including the 50 pa pressure differential as required by Provincial and National Building Codes. They are approved for use in multi-family residential, commercial, utility and industrial projects.



Firestrap




"In-Hole" firestop device that has preformed 3M™ Interam™ Ultra GS Wrap material in a foil encapsulated package that is wrapped around the pipe and fitted into the substrate.

Available Sizes:
1-1/2", 2" and 3"



Ultra Plastic Pipe Device

Ultra Plastic Pipe Device is red coloured, contains 3M™ Interam™ Ultra GS wrap material in a preformed collar. When exposed to temperatures of 121°C the wrap material expands (up to 25 times) to seal combustible pipe service penetrations.



Available Sizes:
1-1/2", 2", 3", 4" and 6"



Products are manufactured by 3M and distributed by IPEX Inc.

PIMENAIP131212
© 2013 IPEX

IPEX Inc.
Toll Free: (866) 473-9462
www.ipexinc.com

Cast-In-Place Device

Fire Barrier Cast-in-Place device is a one piece plastic body assembly. Easily adjustable bodies can be adapted to concrete height, simply with a pair of pliers.



IC 15WB+ Sealant

The IC 15WB+ is an intumescent firestop sealant that is yellow in colour for easy identification. It is used to seal smaller sized DWV penetrations through fire rated substrates.



FS-195+ Wrap Strip

The FS-195+ Wrap Strip is a flexible, reddish brown, foil backed, intumescent (6 to 10 times expansion) material that is used in conjunction with an RC-1 Collar.

Available Sizes:

2" x 24" x 1/4" thick strips



Ultra GS Intumescent Wrap Strip

The Ultra GS Wrap Strip is a flexible, black coloured, highly intumescent (25 times expansion) material. It can be used to seal combustible PEX pipe applications as well.

Available Sizes:

2" x 40' x 1/8" thick rolls



FireDam™ 150+ Caulk

FireDam™ 150+ Caulk is an acrylic, blue or limestone coloured, latex-based, non-sag, paintable sealant that bonds to most construction materials including concrete, metals, wood and cable jacketing.



RC-1 Collar

The RC-1 Collar is a 28 gauge steel preformed collar that is cut to size and is used in conjunction with the Ultra GS Wrap Strip and the FS-195+ Wrap Strip.

