

Valves

NON-FREEZE WALL HYDRANTS - QUARTER TURN - ANTI-SIPHON

- Lead free silver soldered construction
- 3/4" hose thread outlet
- Chrome plated body & tube, built in lockshield
- Notched flange for stable installation
- Built in backflow preventer, automatic draining
- Quarter turn operation makes positive shutoff easy
- CSA certified
- Meets NSF 61-9 low lead standards
- -18° to 82°C temperature range, 125 PSI

PART NO.	TYPE	SIZE	INNER	MASTER
1104-551	1/2" Male x 1/2" Solder	4"	1	20
1104-553	1/2" Male x 1/2" Solder	6"	1	20
1104-555	1/2" Male x 1/2" Solder	8"	1	20
1104-557	1/2" Male x 1/2" Solder	10"	1	20
1104-559	1/2" Male x 1/2" Solder	12"	1	20
1104-561	1/2" Male x 1/2" Solder	14"	1	20
1104-711	1/2" PEX	4"	1	20
1104-713	1/2" PEX	6"	1	20
1104-715	1/2" PEX	8"	1	20
1104-717	1/2" PEX	10"	1	20
1104-719	1/2" PEX	12"	1	20
1104-721	1/2" PEX	14"	1	20

NON-FREEZE WALL HYDRANTS - ANTI-SIPHON

- Lead free silver soldered construction
- 3/4" hose thread outlet
- Chrome plated body & tube, built in lockshield
- Notched flange for stable installation
- Built in backflow preventer, automatic draining
- CSA certified
- Meets NSF 61-9 low lead standards

PART NO.	TYPE	SIZE	INNER	MASTER
1392-040	1/2" Male x 1/2" Solder	4"	2	20
1392-060	1/2" Male x 1/2" Solder	6"	2	20
1392-080	1/2" Male x 1/2" Solder	8"	2	20
1392-100	1/2" Male x 1/2" Solder	10"	2	20
1392-120	1/2" Male x 1/2" Solder	12"	2	20
1392-140	1/2" Male x 1/2" Solder	14"	2	20
1393-080	1/2" PEX	8"	2	20
1393-100	1/2" PEX	10"	2	20
1393-120	1/2" PEX	12"	2	20
1393-140	1/2" PEX	14"	2	20

NON-FREEZE WALL HYDRANTS - ANTI-SIPHON PUSH-FIT

- Lead free silver soldered construction
- 3/4" hose thread outlet
- Notched flange for stable installation
- Built in backflow preventer, automatic draining
- cUPC certified
- Meets NSF 61-9 low lead standards
- -18° to 82°C temperature range, 125 PSI

PART NO.	TYPE	SIZE	INNER	MASTER
1394-080	1/2" Push-Fit	8"	6	24
1394-100	1/2" Push-Fit	10"	6	24
1394-120	1/2" Push-Fit	12"	6	24
1394-140	1/2" Push-Fit	14"	6	24

NEW