

## SC-2 Stainless Steel Service Saddle (Double Bolt)

SC-2 SS Service Saddle



For more information contact,  
Canada Pipeline Accessories

**604 856-7250**

## SC-2 Stainless Steel Service Saddle (Double Bolt)

### Material Specifications

\* SC-2 Stainless Steel Saddles are fully warranted for use on HDPE, (DR9, DR11, DR17), C-900, Asbestos Cement Pipe, SDR35 and IPS PVC pipe only, not for use on metal pipe.

|                      |                                                                                        |
|----------------------|----------------------------------------------------------------------------------------|
| Bolts                | 304 stainless steel, 5/8" roll NC thread.                                              |
| Bolt & Receiver Bars | 304 stainless steel. TIG welded to shell to form a strong fusion and fully passivated. |
| Shell                | 304 stainless steel.                                                                   |
| Locking Washer Plate | 304 stainless steel. Locks into position for easy tightening of nuts.                  |
| Nuts                 | 304 stainless steel & fluorokote coating.                                              |
| Washer               | 304 stainless steel washers are used to reduce wear on washer plate.                   |
| Gasket               | SBR Rubber - ASTM D 2000 AA4 15 Rubber is especially formulated for water service.     |

| ¾" & 1" NPT & CC    |                  |             |           |                 |                 | List Price Per Saddle |        |        |        |
|---------------------|------------------|-------------|-----------|-----------------|-----------------|-----------------------|--------|--------|--------|
| Nom. Size in Inches | Catalogue Number | O.D. Range  | Shell Wt. | Width in Inches | Weight each Lb. | ¾" IP                 | 1" IP  | ¾" CC  | 1" CC  |
| 3                   | SC2-0350-TAP     | 3.40-3.70   | 20 gauge  | 5               | 3               | 77.48                 | 82.80  | 85.61  | 90.36  |
| 4                   | SC2-0485-TAP     | 4.45-4.85   | 20 gauge  | 5               | 3               | 76.41                 | 81.31  | 84.97  | 89.23  |
| 4                   | SC2-0535-TAP     | 4.95-5.35   | 20 gauge  | 5               | 3               | 79.48                 | 84.38  | 88.04  | 92.30  |
| 6                   | SC2-0700-TAP     | 6.54-7.00   | 20 gauge  | 5               | 5               | 82.16                 | 87.76  | 91.29  | 95.58  |
| 6                   | SC2-0745-TAP     | 6.99-7.45   | 20 gauge  | 5               | 5               | 85.23                 | 90.83  | 94.36  | 98.65  |
| 8                   | SC2-0908-TAP     | 8.63-9.08   | 20 gauge  | 5               | 6               | 91.41                 | 93.59  | 94.64  | 98.99  |
| 8                   | SC2-0967-TAP     | 9.21-9.67   | 20 gauge  | 5               | 6               | 94.48                 | 96.66  | 97.70  | 102.06 |
| 10                  | SC2-1116-TAP     | 10.70-11.16 | 18 gauge  | 5               | 6               | 105.28                | 109.69 | 113.23 | 117.60 |
| 10                  | SC2-1221-TAP     | 11.75-12.21 | 18 gauge  | 5               | 6               | 108.35                | 112.76 | 116.30 | 120.67 |
| 12                  | SC2-1321-TAP     | 12.74-13.21 | 18 gauge  | 5               | 7               | 110.56                | 115.37 | 118.90 | 123.29 |
| 12                  | SC2-1447-TAP     | 14.00-14.47 | 18 gauge  | 5               | 7               | 113.63                | 118.44 | 121.97 | 126.36 |

\* Torque bolts to 60 Ft. Lbs.

For more information contact,  
Canada Pipeline Accessories

**604 856-7250**

## SC-2 Stainless Steel Service Saddle (Double Bolt)

### Material Specifications

\* SC-2 Stainless Steel Saddles are fully warranted for use on HDPE, (DR9, DR11, DR17), C-900, Asbestos Cement Pipe, SDR35 and IPS PVC pipe only, not for use on metal pipe.

|                      |                                                                                        |
|----------------------|----------------------------------------------------------------------------------------|
| Bolts                | 304 stainless steel, 5/8" roll NC thread.                                              |
| Bolt & Receiver Bars | 304 stainless steel. TIG welded to shell to form a strong fusion and fully passivated. |
| Shell                | 304 stainless steel.                                                                   |
| Locking Washer Plate | 304 stainless steel. Locks into position for easy tightening of nuts.                  |
| Nuts                 | 304 stainless steel & fluorokote coating.                                              |
| Washer               | 304 stainless steel washers are used to reduce wear on washer plate.                   |
| Gasket               | SBR Rubber -ASTM D 2000 AA4 15 Rubber is especially formulated for water service.      |

| 1-¼", 1½" & 2" NPT & CC |                  |             |           |                 |                 | List Price Per Saddle |        |              |        |
|-------------------------|------------------|-------------|-----------|-----------------|-----------------|-----------------------|--------|--------------|--------|
| Nom. Size in Inches     | Catalogue Number | O.D. Range  | Shell Wt. | Width in Inches | Weight each Lb. | 1¼"-1½" IP            | 2" IP  | 1¼"-1½" CC   | 2" CC  |
| 3                       | SC2-0350-TAP     | 3.40-3.70   | 20 gauge  | 5               | 3               | 115.23                | n/a    | 1¼" - 138.31 | n/a    |
| 4                       | SC2-0485-TAP     | 4.45-4.85   | 20 gauge  | 7½              | 3               | 115.23                | 129.26 | 138.31       | 148.55 |
| 4                       | SC2-0535-TAP     | 4.95-5.35   | 20 gauge  | 7½              | 3               | 119.06                | 133.10 | 142.15       | 152.38 |
| 6                       | SC2-0700-TAP     | 6.54-7.00   | 18 gauge  | 7½              | 5               | 124.14                | 138.31 | 147.44       | 157.65 |
| 6                       | SC2-0745-TAP     | 6.99-7.45   | 18 gauge  | 7½              | 5               | 127.99                | 142.15 | 151.28       | 161.49 |
| 8                       | SC2-0908-TAP     | 8.63-9.08   | 18 gauge  | 7½              | 6               | 132.33                | 146.40 | 155.63       | 165.82 |
| 8                       | SC2-0967-TAP     | 9.21-9.67   | 18 gauge  | 7½              | 6               | 136.16                | 150.23 | 159.47       | 172.72 |
| 10                      | SC2-1116-TAP     | 10.70-11.16 | 18 gauge  | 7½              | 6               | 144.09                | 154.37 | 163.67       | 173.76 |
| 10                      | SC2-1221-TAP     | 11.75-12.21 | 18 gauge  | 7½              | 6               | 147.93                | 158.22 | 167.51       | 177.59 |
| 12                      | SC2-1321-TAP     | 12.74-13.21 | 18 gauge  | 7½              | 7               | 147.97                | 161.95 | 171.19       | 181.35 |
| 12                      | SC2-1447-TAP     | 14.00-14.47 | 18 gauge  | 7½              | 7               | 151.82                | 165.78 | 175.03       | 185.18 |

\* Torque bolts to 60 Ft. Lbs.

For more information contact,  
Canada Pipeline Accessories

**604 856-7250**